



UNIT : mm

NO.	TYPE	A	A1	A2	A3	D	D1	D2	H	H1	H2	H3
1	JS750S	354	258	96	198	180	90	90	529	473	157	38
2	JST8S	354	258	96	198	180	90	90	469	413	157	38
3	JS750SK	354	258	96	198	180	90	90	529	473	157	38
4	JST8SK	354	258	96	198	180	90	90	469	413	157	38
5	GS1200	348	251	97	191	170	85	85	535	479	152	43
6	GST12	348	251	97	191	170	85	85	476	420	152	43
7	GS1500	355	258	97	198	180	85	95	582	526	152	43
8	GST15	355	258	97	198	180	85	95	514	458	152	43
9	GST22	389	284	105	224	206	100	106	611	514	152	59
10	GST37	389	284	105	224	206	100	106	626	529	152	59
11	JS250SV	312	238	74	178	135	64	71	407	377	176	56
12	JS400SV	312	238	74	178	135	64	71	452	422	176	56
13	JST4SV	312	238	74	178	135	64	71	407	377	176	56
14	JS650SV	325	243	82	183	150	73	77	496	440	172	48

UNSPECIFIED TOLERANCES: ANGULAR: $\pm 0^\circ 30'$ LINEAR: PLASTIC MOULDING: ± 0.3 OTHERWISE: REFER TO LINKED FILE	DATE: 2016-11-28	久欣電機股份有限公司 JOUNG SHIN ELECTRIC CORP.	THIRD ANGLE PROJECTION		
	DRAWN: LU		MATERIAL:		
	CHECKED: HUANG	SCALE: 1 : 4	TITLE: SR50-U雙軌著脫與幫浦安裝尺寸圖 SR50-U Double-rail slide rail pump installation dimensional drawing.	A3	A